

Adhesive and Seaming Products Application Directions

PREPARATION: Subfloors must be structurally sound, dry, smooth, clean, and free of dust, dirt, wax, paint, grease, curing agents & any material that might prevent good bond. Concrete must be fully cured (about 28 days or longer after pouring), free of moisture and alkalinity. Make standard moisture and alkalinity tests if necessary.

NOTE: It is the responsibility of the flooring contractor to determine the dryness of all concrete subfloors before installation of floor covering begins. Ongrade concrete subfloors must contain an effective, permanent moisture barrier. Below-grade concrete subfloors must be free of hydrostatic pressure. Maintain floor covering and room at stable temperature of at least 65°F (18°C) for 24 hours before and following installation. All holes, cracks and depressions must be filled with latex underlayment and cracks and depressions must be eliminated. Dust should be removed with a vacuum or wet mop immediately before applying adhesive.

APPLICATION: Apply adhesive with a short nap roller, brush or finishing trowel. To assure proper coverage pour one quart adhesive into corner of a premeasured 12 sq. yd. area and work the pool within the area to determine proper coverage pattern for remainder of the job. Open time is unlimited. Keep applied adhesive free of dust. When adhesive has turned from milky white to clear and will not transfer to touch of finger, proceed to install in accordance with manufacturer's instructions.

APPLICATION: For double stick, releasable or permanent pad installations contact Better Life Technology, LLC for roller, trowel and spray application recommendation.

RECOMMENDED COVERAGE: 11-45 Square yards per gallon, depending on condition of subfloor.

CLEANUP AND STORAGE: Clean up accident spills on face of squares or other surfaces by blotting or wiping with a wet cloth before adhesive dries. Use TAC 244 Safety Solvent for dried adhesive. Soak tools in water and peel or use solvent. Store in cool, dry place. Close container tightly after each use.

DESCRIPTION: G-Floor® Adhesive an easily applied pressure-sensitive type acrylic-emulsion adhesive formulated for installation of G-Floor® floor covering products. Unlimited open time with unlimited tack. Permits easy removal of squares for access to header ducts, communication, electrical and similar access plates and for replacement of worn or damaged sections. May be used over most structurally sound, moisture-free interior subfloors. This adhesive is non-flammable and freeze thaw stable above 0°F or – 18°C. Protect from freezing—do not store outdoors. If frozen, thaw completely at room temperature before stirring—determine suitability of this adhesive before attempting a complete installation.

WARRANTY: This premium adhesive is manufactured according to exacting quality control standards and warranted to be free from manufacturing defects. Defective material called to our attention within one year from purchase will be replaced with valid proof of purchase date. Buyer assumes all risk of use, handling, and storage of product not in strict accordance with label directions. No express warranty is given regarding the performance of this product, since the manner and conditions of application are beyond our control. Any implied warranty of merchantability of fitness for particular use is limited to one year from date of purchase. If used for other than professional purposes, any implied warranty of merchantability or fitness for particular use is excluded. Liability for any incidental or consequential damage or loss is specifically excluded at all times.

FOR PROFESSIONAL USE ONLY

CLEAR - G-Floor Adhesive 4 gal

ENVIRONMENTALLY SAFE PRESSURE SENSITIVE ADHESIVE

Formulated for bonding vinyl floor tiles, roll-out flooring, & carpet squares

CAUTION: DO NOT TAKE INTERNALLY. IF SWALLOWED, CALL A PHYSICIAN IMMEDIATELY—DO NOT INDUCE VOMITING. KEEP OUT OF THE REACH OF CHILDREN. USE WITH ADEQUATE VENTILATION.